# Environmental Product Declaration

THE INTERNATIONAL EPD® SYSTEM



ECO PLATFORM

In accordance with ISO 14025:2006 and EN 15804:2012+A2:2019/AC:2021 for:

# Wood floor lacquer



from

Bona

# Bona®

Programme: Programme operator: EPD registration number: Publication date: Valid until: The International EPD<sup>®</sup> System, <u>www.environdec.com</u> EPD International AB EPD-IES-0016513 2024-09-16 2029-09-15

An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at <u>www.environdec.com</u>



# **General information**

### Programme information

Programme:	The International EPD <sup>®</sup> System			
Address:	EPD International AB Box 210 60 SE-100 31 Stockholm Sweden			
Website:	www.environdec.com			
E-mail:	info@environdec.com			

#### Accountabilities for PCR, LCA and independent, third-party verification

#### Product Category Rules (PCR)

CEN standard EN 15804 serves as the Core Product Category Rules (PCR)

Product Category Rules (PCR): Construction Products PCR 2019:14 version 1.3.4

PCR review was conducted by: Martin Erlandsson, IVL Swedish Environmental Research Institute, Martin.Erlandsson@ivl.se

Life Cycle Assessment (LCA)

LCA accountability: Amit Lotan, Carbonzero AB, Amit.lotan@carbonzero.se

Third-party verification

Independent third-party verification of the declaration and data, according to ISO 14025:2006, via:

□ EPD verification by an individual verifier

Third-party verifier: Stephen Forson, Viridis Pride Ltd, S.Forson@viridispride.com

Approved by: The International EPD<sup>®</sup> System

Procedure for follow-up of data during EPD validity involves third-party verifier:

🗆 Yes 🛛 🖾 No

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but registered in different EPD programmes, or not compliant with EN 15804, may not be comparable. For two EPDs to be comparable, they must be based on the same PCR (including the same version number) or be based on fully-aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have equivalent system boundaries and descriptions of data; apply equivalent data quality requirements, methods of data collection, and allocation methods; apply identical cut-off rules and impact assessment methods (including the same version of characterisation factors); have equivalent content declarations; and be valid at the time of comparison. For further information about comparability, see EN 15804 and ISO 14025.

#### **Company information**

Owner of the EPD: Bona, Ltd

Contact: Bjorn Johansson, Bjorn.Johansson@bona.com

<u>Description of the organization</u>: Bona AB is a company that produces and sells products for floor coating, maintenance, and refurbishment of floors. Bona wishes to understand the environmental impacts of its floor coating chemicals used to refurbish old flooring and make this information publicly available as an EPD

Name and location of production site(s): Malmö, Sweden

#### **Product information**

<u>Product name:</u> Traffic GO <u>Product identification</u>: Wood floor lacquer <u>Product Description</u>: waterborne lacquer with a built-in hardener <u>UN CPC code</u>: 35110 <u>Geographical scope</u>: Raw materials are sourced mainly from within Europe. Manufacturing is in Sweden. Products are sold worldwide.


#### Technical specification:

Product type: Self-crosslinking waterborne polyurethane topcoat Solids content: Approx. 30% Sheen (at 60°): Silkmatt 45-50%, Matt 20-25%, Extra Matt 9-13%, Ultra matt approx. 5% (on glass) Dilution: If required, dilute with 4% Bona Retarder for a longer open time Drying time until Recoating: 2-3 hours\* Full use: 24 hours\* Possible to cover: 3 days\* Application tools: Bona Roller or Swivel Head Applicator Application rate: 8-10 m2/liter (100-120g/m2) per coat \*under normal climate conditions, 20°C/60% R.H.

#### LCA information

<u>Functional unit / declared unit:</u> 1 kg of coating material, Produced and Packed <u>Reference service life:</u> 15 years <u>Time representativeness:</u> Manufacturing data from 2023. <u>Database(s) and LCA software used:</u> SimaPro v9.5, Ecoinvent 3.10 <u>Description of system boundaries:</u> Cradle-to-gate with options, modules A1-A3, A4 <u>Allocation:</u> the plant produces a range of chemicals. Actual manufacturing data for A3 was recorded for 2023. The allocation used a combination of economic (where feasible) and mass allocation by the accounting and production teams.

System diagram:



#### More information:

#### Manufacturing Description:


The manufacturing process can vary depending on the type of intended application. It consists of mainly:

- Mixing and Heating: Select resins are mixed with water and in specific ratios. The mixture is heated to dissolve all components properly and facilitate mixing.
- Filtration: The mixture is filtered to remove impurities or undissolved particles, ensuring a smooth and consistent final product.
- Quality Control: Quality checks ensure the products meet the desired specifications.
- Packaging: The final product is packed in various sizes and sent to warehouses for storage and dispatch.

<u>A3 electricity</u>: Bona specifies the electricity mix used for 2023. It has a climate change total of 0.005 kg CO2e per kWh.

Bona produces solar electricity (5,3% of the total) and buys wind (94,6%).

Bona's heating comes from their bought Biogas, used for heating in manufacturing vessels.



Supplier waste is being disposed of in this stage.

- Solid waste is disposed of as municipal waste
- Wastewater is treated in nearby treatment facility WWP

Plastic and Cardboard are disposed of in municipal incineration

<u>A4 transport to global sellers -</u> The products are sold worldwide. A weighted average transport distance was calculated and used.

	Truck	Ship
Vehicle and fuel types	Truck-trailer, Euro 0 - 6 mix, 34 - 40t gross weight / 27t payload capacity Using 0.021 kg diesel per tkm	Container ship, 5.000 to 200.000 dwt payload capacity, deep sea Using 0.0027 kg heavy fuel oil per tkm
Distance /km	200	100
Capacity utilisation /%	61 Dataset default value	70 Dataset default value
Bulk density of transported products/kg/m <sup>3</sup>	1000	1000
Volume capacity utilization factor	1	1

#### Modules declared, geographical scope, Specific data used.

	Pro	duct sta	age	Constr proc sta				U	se sta	ge			En	d-of-li	ife sta	ge	Resource recovery stage
	Raw material supply	Transport	Manufacturing	Transport	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling- potential
Module	A1	A2	A3	A4	A5	B1	B2	В3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	х	х	х	х	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Geography	GLO	GLO	SE	GLO	-	-	-	-	-	-	-	-	-	-	-	-	-
Specific data used		~10 %		-	-	-	-	-	-	-	-	-	-	-	-	-	-
Product Variation		0%		-	-	-	-	-	-	-	-	-	-	-	-	-	-
Site Variation		0%		-	-	-	-	-	-	-	-	-	-	-	-	-	-

# **Content information**

Product Components	Weight, kg	Post-consumer material, weight-%	Biogenic material, weight-% and kg C/kg
Water	0.7	0	0
Organic Chemicals	0.2	0	0
Additives	0.1	0	0
TOTAL	1	0	0
Packaging materials	Maximum weight, kg	Weight-% (versus the product)	Weight biogenic carbon, kg C/kg
Paper and board	2.43E-03	0.2 %	1.04E-03
Plastic	5.63E-02	5.6 %	0
Pallet	9.21E-04	0.1 %	5.34E-04
TOTAL	5.97E-02	5.9 %	1.58E-03

None of the raw materials used in this product, and at the time of production of the EPD, fall within the Candidate List of Substances of Very High Concern for the Authorization of the European Chemicals Agency. In any case, the eventual presence of Substances of Very High Concern would be reported in the safety data sheets for each product/product group.

# **Results of the Environmental Performance Indicators**

Using EN15804 reference package EF3.1

	-	•••	Results per fu	nctional or dec	clared unit		
Indicator	Unit	Total	A1	A2	A3	A1-A3	A4
GWP-fossil	kg CO <sub>2</sub> eq.	3.50E+00	3.04E+00	8.40E-02	1.14E-01	3.24E+00	2.67E-01
GWP-biogenic	kg CO <sub>2</sub> eq.	0	-8.51E-03	0	8.51E-03	0.00E+00	0
GWP-luluc	kg CO <sub>2</sub> eq.	3.82E+00	3.09E+00	8.39E-02	3.78E-01	3.55E+00	2.66E-01
GWP- total	kg CO <sub>2</sub> eq.	3.37E-02	3.26E-02	4.12E-05	9.02E-04	3.35E-02	1.37E-04
ODP	kg CFC 11 eq.	2.55E-05	2.54E-05	1.83E-09	3.43E-09	2.54E-05	5.66E-09
AP	mol H⁺ eq.	1.87E-02	1.47E-02	3.63E-04	1.88E-03	1.69E-02	1.74E-03
EP-freshwater	kg P eq.	1.20E-04	1.00E-04	6.73E-07	1.69E-05	1.18E-04	2.04E-06
EP-marine	kg N eq.	3.73E-03	2.63E-03	1.35E-04	4.06E-04	3.17E-03	5.63E-04
EP-terrestrial	mol N eq.	3.95E-02	2.75E-02	1.45E-03	4.45E-03	3.34E-02	6.12E-03
POCP	kg NMVOC eq.	1.49E-02	1.07E-02	5.18E-04	1.59E-03	1.28E-02	2.02E-03
ADP- minerals&metals*	kg Sb eq.	1.96E-05	1.69E-05	2.70E-07	1.71E-06	1.89E-05	8.05E-07
ADP-fossil*	MJ	7.16E+01	5.80E+01	1.20E+00	8.65E+00	6.79E+01	3.75E+00
WDP*	m <sup>3</sup>	1.98E+00	1.86E+00	4.86E-03	9.94E-02	1.96E+00	1.47E-02
Acronyms		Potential bio change; OD potential, Ac of nutrients r	= Global Warmir genic; GWP-lulu P = Depletion po coumulated Exce reaching freshwa iction of nutrients	uc = Global War otential of the st edance; EP-fre ater end compa	ming Potential ratospheric ozc shwater = Eutro rtment; EP-mar	land use and la one layer; AP = , ophication poter ine = Eutrophic	nd use Acidification ntial, fraction ation

## Mandatory impact category indicators according to EN 15804

(user) deprivation potential, deprivation-weighted water consumption Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator.

potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water

## Additional mandatory and voluntary impact category indicators

		Results per functional or declared unit						
Indicator	Unit	Total	A1	A2	A3	A1-A3	A4	
GWP-GHG <sup>1</sup>	kg CO <sub>2</sub> eq.	3.82E+00	3.09E+00	8.39E-02	3.78E-01	3.55E+00	2.66E-01	

#### **Resource use indicators**

		Results per functional or declared unit							
Indicator	Unit	Total	A1	A2	A3	A1-A3	A4		
PERE	MJ	9.83E+00	3.99E+00	1.85E-02	5.77E+00	9.78E+00	5.56E-02		
PERM	MJ	3.03E-01	1.34E-01	0.00E+00	1.69E-01	3.03E-01	0.00E+00		
PERT	MJ	1.01E+01	4.12E+00	1.85E-02	5.94E+00	1.01E+01	5.56E-02		
PENRE	MJ	5.61E+01	4.70E+01	1.20E+00	4.15E+00	5.24E+01	3.75E+00		
PENRM	MJ	1.55E+01	1.10E+01	0.00E+00	4.50E+00	1.55E+01	0.00E+00		
PENRT	MJ	7.16E+01	5.80E+01	1.20E+00	8.65E+00	6.79E+01	3.75E+00		
SM	kg	9.21E-04	0	0	9.21E-04	9.21E-04	0		
RSF	MJ	0	0	0	0	0	0		
NRSF	MJ	0	0	0	0	0	0		
FW	m³	5.31E-02	4.97E-02	1.70E-04	2.67E-03	5.25E-02	5.15E-04		
Acronyms		used as raw materials; Pl renewable p materials; Pl	materials; PER ERT = Total use rimary energy e ENRM = Use of	M = Use of rene of renewable p excluding non-ren non-renewable	wable primary er rimary energy res newable primary primary energy re	ble primary energy nergy resources us sources; PENRE = energy resources esources used as rces; SM = Use of	sed as raw = Use of non- used as raw raw materials;		

PENRT = Total use of non-renewable primary energy re-sources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator

<sup>&</sup>lt;sup>1</sup> This indicator accounts for all greenhouse gases except biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. As such, the indicator is identical to GWP-total except that the CF for biogenic  $CO_2$  is set to zero.

## Waste indicators

Results per functional or declared unit							
Indicator	Unit	Total	A1	A2	A3	A1-A3	A4
Hazardous waste disposed	MJ	1.68E-05	1.68E-05	0	0	1.68E-05	0
Non-hazardous waste disposed	MJ	2.26E-02	2.26E-02	1.25E-06	5.51E-05	2.27E-02	3.84E-06
Radioactive waste disposed	MJ	3.19E-06	3.19E-06	0	0	3.19E-06	0

## Output flow indicators

Results per functional or declared unit								
Indicator	Unit	Total	A1	A2	A3	A1-A3	A4	
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	
Material for recycling	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	
Materials for energy recovery	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	
Exported energy, electricity	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	
Exported energy, thermal	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	

### Disclaimers

The estimated impact results are only relative statements, which do not indicate the endpoints of the impact categories, exceeding threshold values, safety margins, and risks.

ILCD classification	Indicator	Disclaimer	
	Global warming potential (GWP)	None	
ILCD Type 1	Depletion potential of the stratospheric ozone layer (ODP)	None	
	Potential incidence of disease due to PM emissions (PM)	None	
	Acidification potential, Accumulated Exceedance (AP)	None	
	Eutrophication potential, Fraction of nutrients reaching	None	
	freshwater end compartment (EP-freshwater)	None	
	Eutrophication potential, Fraction of nutrients reaching	None	
ILCD Type 2	marine end compartment (EP-marine)	None	
	Eutrophication potential, Accumulated Exceedance	None	
	(EP-terrestrial)	NULLE	
	Formation potential of tropospheric ozone (POCP)	None	
	Potential Human exposure efficiency relative to U235 (IRP)	1	
	Abiotic depletion potential for non-fossil resources (ADP-minerals&metals)	2	
	Abiotic depletion potential for fossil resources (ADP-fossil)	2	
	Water (user) deprivation potential, deprivation-weighted	2	
	water consumption (WDP)	2	
ILCD Type 3	Potential Comparative Toxic Unit for ecosystems (ETP-fw)	2	
	Potential Comparative Toxic Unit for humans (HTP-c)	2	
	Potential Comparative Toxic Unit for humans (HTP-nc)	2	
	Potential Soil quality index (SQP)	2	

Disclaimer 1 – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator.

## References

EN 15804:2012+A2	Sustainability of construction works – Environmental product declaration – Core rules for the product category of construction products
EPD International (2024)	General Programme Instructions International EPD® System, version 5.0
EPD S-P-01434	Amotherm water-based coatings, 2019, published on EPD International https://www.environdec.com/library/epd1434
EPD S-P-01822	Boero Coatings, 2020, published on EPD International https://www.environdec.com/library/epd1822
ISO 14020:2022	International Standard ISO 14020 – Environmental statements and programs for products – Principles and general requirements
ISO 14025:2006	International Standard ISO 14025 – Environmental labels and declarations — Type III environmental declarations — Principles and procedures
ISO 14040:2006	International Standard ISO 14040: Environmental Management – Life cycle assessment – Principles and framework. Second edition 2006-07-01.
PCR 2019:14	Construction products v1.3.4

